



The New IP Matrix Range


IP-SS-MPT-012 2MP IR Dome Camera



Main Features Include:

- 1 / 1.9" 2 Megapixel Progressive Scan CMOS
- H.265 & H.264 Triple-stream Encoding
- 50 / 60fps @ 1080P (1920×1080)
- WDR (120dB), Day / Night (ICR), 3DNR, AWB, AGC, BLC
- Multiple Network Monitoring: Web Viewer, CMS(DSS/PSS) & DMSS
- 4.1mm ~ 16.4mm Motorised Lens
- Max. IR LEDs Length 50m
- Micro SD Memory, IP67, IK10, POE
- 316L Stainless Steel Housing

Dimensions:



Camera Information:

The 2MP IR Dome Camera low-light performance delivers usable video with minimal ambient light. Even in extreme low-light conditions, & in near complete darkness (0.002 lux) it is capable of delivering colour images

For applications with both bright and low lighting conditions that change quickly, True WDR (120dB) optimises both the bright and dark areas of a scene at the same time to provide usable video

The built-in video will quickly & accurately respond to monitoring events

It enhances monitoring efficiency, & at the same time, The camera can support face detection, it can quickly capture a face & upload the image to the server

In addition the camera also supports intelligent tamper detection, through dramatic changes in the scene it will send out warning information to ensure effective monitoring

Specification may change without prior notice





The New IP Matrix Range

IP-AT-01-W-4MP Low Profile Dome Camera



Technical Data

Camera	Image Sensor	1 / 1.9" 2Megapixel progressive scan CMOS	
	Effective Pixels	1920 (H) x 1080 (V)	
	RAM / ROM	1024MB / 128MB	
	Scanning System	Progressive	
	Minimum Illumination	0.002Lux/F1.53(Color), 0Lux/F1.53(IR on)	
	S/N Ratio	More than 50dB	
	IR Distance	Up to 50m (164ft)	
	IR On/Off Control	Auto/ Manual	
	IR LEDs	3	
Lens	Lens Type	Motorised / Auto Iris (HALL)	
	Mount Type	Board-in	
	Focal Length	4.1 ~ 16.4mm motorised	
	Max Aperture	F1.53	
	Angle of View	H: 92° ~ 32° V:53° ~ 18°	
	Optical Zoom	4x	
	Focus Control	Motorised	
	Close Focus Distance	1m (3.28ft)	
	Pan / Tilt / Rotation Range	Pan: 0° ~ 355°; Tilt: 0° ~ 65°; Rotation:0° ~ 355°	
Video	IVS (optional)	Tripwire, Intrusion, Object Abandoned / Missing	
	Advanced Intelligent Functions	Face Detection, People Counting, Heat Map	
	Bit Rate Control	CBR / VBR	
	Bit Rate	H.264: 24~ 10240Kbps H.265: 14~ 6144Kbps	
	Day / Night	Auto (ICR) / Colour / B/W	
	BLC Mode	BLC / HLC / WDR (120dB) / SSA	
	White Balance	Auto / Natural / Street Lamp / Outdoor / Manual	
	Gain Control	Auto / Manual	
	Noise Reduction	3D DNR	
	Motion Detection	Off / On (4 Zone, Rectangle)	
	Region of Interest	Off / On (4 Zone)	
	Electronic Image Stabilisation,	Support	
	Smart IR & Defog		
	Digital Zoom	16x	
Aux	Flip	0°/ 90°/ 180°/ 270°	
	Mirror	Off / On	
	Privacy Masking	Off / On (4 Area, Rectangle)	
	Audio - Compression	G.711a / G.711Mu / AAC / G.726	
	Ethernet Protocol	RJ-45 (100 / 1 000Base-T)	
		HTTP; HTTPs; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP; NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP	
	General	Inter-operability	ONVIF, PSIA, CGI
		Streaming Method	Unicast / Multicast
		Max. User Access	10 Users / 20 Users
		Edge Storage	NAS, Local PC for instant recording, Mirco SD card 128GB
Web Viewer		IE, Chrome, Firefox, Safari	
Management Software Smart Phone		Smart PSS, DSS, Easy4ip IOS, Android	

